



(WLL) Capacity from Vertical and Perpendicular to the Beam

Inch & Lbs.						A	B				F			Weight
		@ 0°	@ 15°	@ 30°	@ 45°	Adjustment	Max	C	D	E	Max	H	Lbs.	
1t	BC-01	2,200	0	0	0	3.1 - 9.4	14.6	3.7	0.75	7.8	5.7	0.8	7.7	
	BCD-01	2,200	1,800	1,500	1,100					8.7	7.8	1.7	9.0	
2t	BC-02	4,400	0	0	0	3.1 - 9.4	14.6	4.0	0.75	7.8	5.7	0.8	9.9	
	BCD-02	4,400	3,700	2,900	2,200					8.7	7.8	1.7	11.0	
3t	BC-03	6,600	0	0	0	3.5 - 12.2	19.7	5.2	1.12	10.4	8.2	0.9	20.9	
	BCD-03	6,600	5,500	4,400	3,300					10.2	11.0	2.4	22.4	
5t	BC-05	11,000	0	0	0	3.5 - 12.2	19.7	5.6	1.41	10.4	8.2	0.9	24.2	
	BCD-05	11,000	9,100	7,300	5,500					10.2	11.0	2.4	26.2	
10t	BC-10	22,000	0	0	0	3.5 - 12.6	20.6	7.1	1.50	11.2	8.7	1.5	35.2	
	BCD-10	22,000	18,300	14,500	11,000					12.0	13.0	3.6	40.5	

